



# SAMSUNG

## SPLIT ESSENTIAL INVERTER

Digital Inverter™



### TABLA TÉCNICA

| BTU                                                |                          | 9000 BTU    | 12000 BTU   | 18000 BTU   | 24000 BTU    |
|----------------------------------------------------|--------------------------|-------------|-------------|-------------|--------------|
| CAPACIDAD FRÍO (BTU)                               |                          | 9.000       | 11.000      | 17.200      | 21.000       |
| CAPACIDAD CALOR (BTU)                              |                          | 9.500       | 11.500      | 17.800      | 21.500       |
| NIVEL DE RUIDO UND. INTERIOR ALTO/BAJO (dB)        |                          | 33/42       | 34/43       | 35/45       | 39/47        |
| REFRIGERANTE                                       |                          | R32         | R32         | R32         | R32          |
| SIN CAJA<br>DIMENSIONES INTERIOR (ancho*prof*alto) |                          | 815x288x195 | 815x288x195 | 920x320x230 | 1100x320x230 |
| SIN CAJA<br>DIMENSIONES EXTERIOR (ancho*prof*alto) |                          | 700x285x540 | 700x285x540 | 793x292x601 | 823x301x650  |
| POTENCIA CONSUMIDA FRÍO/CALOR(W)                   |                          | 792/771     | 1.004/958   | 1.570/1.445 | 1.916/1.745  |
| PESO NETO UND. INT/EXT (KG)                        |                          | 7,6/21      | 7,8/22,5    | 11,5/28     | 12,5/37,5    |
| CAÑERÍA                                            | Largo total máximo (M)   | 15          | 15          | 20          | 20           |
|                                                    | Desnivelación máximo (M) | 10          | 10          | 10          | 10           |

\*Kit instalación: Control remoto, Kit tubería de 4 mt, cable de interconexión en unidad interior y enchufe de 16A.

